


# Specification sheet

# XBC 230

FA 4X2 Rigid, 19t



## ENGINES

- XBC NewGen 230 PX-7 (167 kW / 227 hp)
- XBC NewGen 260 PX-7 (189 kW / 257 hp)
- XBC NewGen 290 PX-7 (212 kW / 287 hp)
- XBC NewGen 310 PX-7 (227 kW / 308 hp)

## GVM<sup>1)</sup>

- 18000 kg
- Max. front 7500 kg
- Max. rear 11500 kg

## GCM<sup>2)</sup>

- 19000 kg

016F5803ABAA - 202501H - 18-09-2024

DAF Trucks Ltd, UK, Haddenham, HP17 8LJ, [www.daf.co.uk](http://www.daf.co.uk)

## CAB EXTERIOR

Day Cab with steel bumper, tinted glass and electric window openers. Main mirrors and wide angle mirrors electrically heated. Cab width 2130 mm.; Electrically adjustable mirrors; Mirror brackets, body 2.50-2.60 m; Front view mirror; Rear view camera.

### Optional

- |   |  |
|---|--|
| <b>01605</b> Cab suspension mechanical reinforced | <b>00915</b> Side no glass / rear single glass |
| <b>06629</b> Two hazard beacon lights             | <b>09101</b> Green tinted glass, heated        |
| <b>02083</b> Two hazard beacon lights LED         | <b>09283</b> Mirror brackets, body 2.40-2.50 m |
| <b>07343</b> Kerb view window co-driver door      |  |

## AERODYNAMICS

### Optional

- |   |  |
|---|--|
| <b>09286</b> Roof air deflector prepared              | <b>07092</b> Adjustable roof air deflector low (set) |
| <b>06776</b> Adjustable roof air deflector            | <b>09287</b> Side collars prepared                   |
| <b>07109</b> Adjustable roof air deflector high (set) | <b>07112</b> Side collars long (set)                 |

## COLOURS

; Head lamp panel and bumper: Stone Grey; Lower step cover, cab steps and wing Stone Grey.; Chassis colour grey..

### Optional

- |   |                                      |
|---|--------------------------------------|
| <b>06485</b> Head lamp panel and bumper: cab colour | <b>16153</b> Cab and chassis colours |
|---|--------------------------------------|

## CAB INTERIOR

Right-hand drive (RHD); Mechanically adjustable steering column; Driver seat: air suspended; Co-driver seat: fixed velour; Storage box on engine tunnel.

### Optional

- |   |   |
|---|---|
| <b>01846</b> Left-hand drive (LHD)                    | <b>00967</b> Seat belts red             |
| <b>09271</b> Steering wheel, leather, colour black    | <b>16158</b> Seat types                 |
| <b>03516</b> Pneumatically adjustable steering column | <b>04246</b> Roof hatch, manual control |

## COMMUNICATION AND DRIVING MANAGEMENT

FMS connector, prepared; Tachograph digital, Stoneridge 1C version G2V2; Driver Performance Assistant.

### Optional

- |   |
|---|
| <b>16155</b> Audio equipment, makes and types |
|---|

## SAFETY AND SECURITY

Speed limit recognition; DAF drowsiness detection; Drive-off Assist.

### Optional

- |  |                                 |
|--|---------------------------------|
| <b>08631</b> Air bag (driver) and 2 seat belt tensioners | <b>01723</b> No reverse warning |
| <b>07414</b> Reverse warning with self-adjusting volume  | <b>16156</b> EC-ADR packages    |

## SUSPENSION AND AXLES

Front axle type 152N, 100 mm vertical offset. Parabolic leaf suspension with shock absorbers and stabiliser. Max. load 7.5 tonnes.; Single reduction driven rear axle type SR1132 with asymmetric parabolic leaf suspension, including shock absorbers. Max. load 11.5 tonnes..

## WHEELS AND TYRES

Front axle(s): 315/80R22.5; Driven rear axle(s): 315/80R22.5; Goodyear; Wheel protection rings silvergrey.

### Optional

- |  |                                   |
|--|-----------------------------------|
| <b>06764</b> Wheel protection rings black        | <b>16152</b> Tyre makes and types |
| <b>06766</b> Wheel protection rings chromium DAF |                                   |

## DRIVELINE

Engine PX-7, 6 cylinder diesel engine, 6.7 litres. Output 167 kW (227 hp) at 1900 rpm. Max. torque 890 Nm at 1000-1700 rpm.; Exhaust emission Euro 6; Manual gearbox, 6 speeds; Gearbox ratio 6.75-0.78; Rear axle ratio 5.13.

### Optional

- |   |                                   |
|---|-----------------------------------|
| <b>04393</b> Manual gearbox, 9 speeds             | <b>02800</b> Rear axle ratio 4.10 |
| <b>07667</b> Automatic gearbox PowerLine, 8-speed | <b>02808</b> Rear axle ratio 4.56 |
| <b>02313</b> Gearbox direct drive                 | <b>03315</b> Rear axle ratio 5.63 |
| <b>01879</b> Rear axle ratio 3.73                 |                                   |

## BRAKE SYSTEM

Exhaust brake.

### Optional

- |   |
|---|
| <b>09524</b> Park brake control with spoken warning |
|---|

## CHASSIS

Wheelbase 3.45 m / rear overhang 1.12 m; Side member height 270 mm; EAS unit right, vertical discharge; Battery box left, no spare wheel carrier; Plastic fuel tank 200 l; Tank for AdBlue® 30 l, right-hand side chassis; No front underrun protection; No spray suppression.

### Optional

- |  |                                   |
|--|-----------------------------------|
| <b>04439</b> Battery box left, spare wheel carrier right | <b>03323</b> Rear light with LEDs |
| <b>07071</b> Spare wheel carrier right-hand side         |                                   |

## DRAWBAR AND TRAILER EQUIPMENT

Closing member D-value = 0kN.

## BODIES AND PREPARATIONS FOR BODYING

Application connector chassis; Standard body attachment hole pattern.

### Optional

- |   |   |
|---|---|
| <b>09952</b> BodyBuilder Module (BBM) full                | <b>09240</b> Application connector for refuse collector |
| <b>06691</b> Application connector on the cab front       | <b>01502</b> No side marker lights                      |
| <b>02950</b> Application connector for hydraulic platform |   |

## POWER TAKE-OFF (PTO)

**Optional**

**06282** Rear eng PTO 13h, permanent, pump drive      **16148** PTO types and positions

**24V POWER SUPPLY**

Alternator 80 A, batteries 2x 125 Ah..

**Optional**

**01897** Alternator 100 A      **08797** Batteries 2x175Ah

**GVM AND GCM**

Chassis weight related technical GVM max 19000 kg; Driveline related technical GCM equal to GVM.

**Optional**

**00064** Driveline related max GCM 22500 kg

**APPLICATION CONDITIONS**

Moisture separator, unheated; Air intake high behind cab.

**Optional**

**02270** Cold climate      **09960** Air intake on the cab roof  
**04767** Moisture separator, heated

**VEHICLE DELIVERY**

Standard toolkit.


**Optional**

**06491** Toolkit Eastern Europe

**Go to [DAF.com](https://www.daf.com) to configure your own perfect DAF.**

# XBC 230

FA 4X2 Rigid, 19t



	Wheelbase - AE		Unladen weight <sup>9)</sup>			Gross Carrying Capacity			Variable dimensions									
	WB	AE <sup>9)</sup>	Front	Rear	Total	Front	Rear	Total	AC	CB <sup>6)</sup>	CH <sup>7)</sup>	BL <sup>8)</sup>	BL	TL	HA <sup>9)</sup>	HA <sup>10)</sup>	TK <sup>11)</sup>	TW <sup>12)</sup>
DAY CAB	3,45	1,12	3412	1714	5126	4088	9786	12874	0,23	0,21	1,88	4,00	4,00	5,96	1,08	0,96	12,96	13,99
	3,75	1,12	3437	1725	5162	4063	9775	12838	0,23	0,21	1,88	4,42	4,42	6,26	1,08	0,97	13,78	14,82
	4,15	1,12	3457	1728	5185	4043	9772	12815	0,23	0,21	1,88	5,00	5,00	6,66	1,08	0,98	14,87	15,93
	4,45	1,12	3478	1741	5220	4022	9759	12780	0,23	0,21	1,88	5,43	5,43	6,96	1,08	0,98	15,69	16,77
	4,75	1,12	3490	1747	5237	4010	9753	12763	0,23	0,21	1,88	5,87	5,87	7,26	1,08	0,98	16,51	17,60

OTHER DIMENSIONS VA: 1,39 HV<sup>13)</sup>: 1,00 HV<sup>14)</sup>: 0,90 RB: 0,79 SB: 1,83 TB<sup>15)</sup>: 2,47

1) GVM in conformity with registration documents.

2) GCM in conformity with registration documents.

3) Axle load with standard tyre size.

4) Chassis and cab weight calculated with: Standard specification items only with 200 litres of fuel, 30 litres of AdBlue® and driver of 90 kg, tolerance ± 3%. Changing of the specification can have major impact on vehicle weight.

5) Other AE dimensions may be available for shown WB. Modify rear overhang to the calculated body length.

6) CB is based on standard air intake and/or exhaust.

7) Cab height is measured from frame member to closed cabin roof hatch.

8) Calculate customer specific body length with TOPEC. Body lengths shown based on evenly distributed load at max axle load.

9) Unladen height at centre of driven axle(s).

10) Laden height at centre of driven axle(s).

11) TK = turning circle between kerbs.

12) TW = turning circle between walls.

13) Unladen height at centre of front axle(s).

14) Laden height at centre of front axle(s).

15) TB is overall width at rear. (At centre of front axle 255).

Depending on the vehicle configuration a specific option may not be possible. The availability and specification of this vehicle may differ per country. For further information please contact the DAF organisation. Pictures and technical illustrations are not binding in detail and can differ from the standard specification. Subject to modification without prior notice.