


Specification sheet

CF 290

FAS 6X2 Rigid, double mounted trailing axle



ENGINES
CF 290 PX-7 (217 kW / 295 hp)
CF 320 PX-7 (239 kW / 325 hp)

GVM ¹⁾	GCM ²⁾
26000 kg	30500 kg
Max. front 8000 kg	
Max. rear 19000 kg	

016F6626AAAA - 2021371 - 11-06-2021

DAF Trucks Ltd, UK, Haddenham, HP17 8LJ, www.daf.co.uk

CAB EXTERIOR

Day Cab with galvanised steel bumper, tinted glass and electric window openers. Main mirrors and wide angle mirrors electrically heated. Cab width 2300 mm.; LED daytime running lights; Electrically adjustable mirrors; Front view mirror.

Optional

02106	Sleeper Cab	09984	Fog lights and cornering lights
01137	Space Cab	06593	Skylights
01174	External sun visor green translucent	06628	One hazard beacon light at co-driver side
08020	LED head lights	06627	One hazard beacon light at driver side
09983	Fog lights	06629	Two hazard beacon lights

AERODYNAMICS

Optional

04906	Side collars
-------	--------------

COLOURS

Cab colour H3279 Brilliant White; Head lamp panel and bumper: Brilliant White; Chassis colour grey..

Optional

06485	Head lamp panel and bumper: cab colour	07245	Mirror covers Brilliant White
09933	Head lamp panel and bumper: Stone Grey	04198	Mirror covers in cab colour
06442	Mirror covers grey	16153	Cab and chassis colours

CAB INTERIOR

Driver seat: Comfort Air; Co-driver seat: basic; Automatic Temperature Control and airco; Pollen filter; Roof hatch glass, manual control.

Optional

09271	Steering wheel, leather, colour black	07741	Co-driver seat: Comfort Air
07240	Steering wheel, leather, Exclusive	07743	Co-driver seat: Luxury Air
07152	Cab interior trim colour Exclusive	07746	Co-driver seat: Super Air
07592	Cab interior decoration Argenta	07748	Co-driver seat: Xtra Leather Air
07591	Cab interior decoration Rustica	00967	Seat belts red
07733	Driver seat: Luxury Air	02117	Third seat
07736	Driver seat: Super Air	06539	Refrigerator
07737	Driver seat: Xtra Leather Air		

COMMUNICATION AND DRIVING MANAGEMENT

Tachograph digital, Stoneridge 1C; Speed limiter setting 85 km/h absolute; Antennas: radio, 2x cellular, GNSS; Adaptive Cruise Control with FCW and AEBS-CM2.

Optional

16155	Audio equipment, makes and types	07261	TruckPhone
-------	----------------------------------	-------	------------

SAFETY AND SECURITY

Lane Departure Warning System; Vehicle Stability Control (VSC); Basic engine immobiliser system.

Optional

01725	Reverse warning	16156	EC-ADR packages
-------	-----------------	-------	-----------------

SUSPENSION AND AXLES

Front axle load 8.00 t; Rear: 12.00 + 7.80 t, air suspension, SR1344; Lifting device.

Optional

06257	Front axle load 9.00 t	08191	Axle load monitoring
00567	Rear axle load 10.00+ 10.00 t	02013	Load limiter 10.0 t

WHEELS AND TYRES

Front axle(s): 315/70R22.5; Driven rear axle(s): 315/70R22.5; Second driven rear or trailing axle: 315/70R22.5; Disc wheels steel, silvergrey; Wheel protection rings silvergrey.

Optional

16152	Tyre makes and types
-------	----------------------

DRIVELINE

Engine PX-7, 6 cylinder diesel engine, 6.7 litres. Output 217 kW (295 hp) at 2300 rpm. Max. torque 1100 Nm at 1000-1700 rpm.; Exhaust emission Euro 6; Engine idle shutdown, 5 minutes; Manual gearbox, 9 speeds; Gearbox ratio 12.73-1.00; Rear axle ratio 4.11.

Optional

04500	AS Tronic gearbox, 12 speeds
-------	------------------------------

CHASSIS

Wheelbase 4.20 m / rear overhang 2.40 m; Side member height 310 mm; Standard component location; Aluminium fuel tank 340 l, height 620 mm; Tank for AdBlue® 50 l, left-hand side chassis; Front underrun protection (FUP); Spray suppression.

Optional

16157	Fuel tanks, material and sizes	07071	Spare wheel carrier right-hand side
-------	--------------------------------	-------	-------------------------------------

DRAWBAR AND TRAILER EQUIPMENT

Closing member.

Optional

07029	D-value cross member D=13.7
-------	-----------------------------

BODIES AND PREPARATIONS FOR BODYING

Application connector on the cab front.

Optional

06692	Application connector chassis	09240	Application connector for refuse collector
02597	Application connector for tail lift control		

POWER TAKE-OFF (PTO)

Optional

16148	PTO types and positions
-------	-------------------------

ELECTRICAL POWER SUPPLY

Alternator 80 A, batteries 2x 140 Ah..

Optional

01897	Alternator 100 A	06440	Batteries 2x230Ah
08797	Batteries 2x175Ah		

GVM AND GCM

Chassis weight related technical GVM max 27000 kg; Driveline related max GCM 30500 kg.

Optional

00807 Driveline related max GCM 31500 kg	00362 Driveline related max GCM 32000 kg
--	--

APPLICATION CONDITIONS

Moisture separator, unheated; Air intake on the cab roof.

Optional

02270 Cold climate	09961 Cyclonic air intake behind the cab
--------------------	--

SERVICE AND MAINTENANCE

Warranty Plus - 2 Year Vehicle & 3 Year Driveline - takes care of all warrantable repairs on the vehicle for two years and on the driveline for a third year together with associated breakdown coverage.; DAF 2 year Preventive Maintenance Package - 320k.



Go to [DAF.com](https://www.daf.com) to configure your own perfect DAF.

CF 290

FAS 6X2 Rigid, double mounted trailing axle

	Wheelbase - AE		Unladen weight ⁴⁾			Gross Carrying Capacity			Variable dimensions										
	WB	AE ⁵⁾	Front	Rear	Total	Front	Rear	Total	AC	CB ⁶⁾	CH ⁷⁾	BL ⁸⁾	BL	TL	HA ⁹⁾	HA ¹⁰⁾	TK ¹¹⁾	TW ¹²⁾	
DAY CAB	3,80	2,05	5045	3786	8831	2955	15214	17169	0,39	0,18	1,94	6,07	6,57	8,62	0,90	0,87	14,93	16,30	
	4,20	2,40	5038	3866	8904	2962	15134	17096	0,39	0,18	1,94	6,72	7,27	9,37	0,90	0,87	15,97	17,36	
	4,40	2,55	5050	3928	8978	2950	15072	17022	0,39	0,18	1,94	7,06	7,62	9,72	0,90	0,87	16,49	17,89	
	4,60	2,75	5046	3971	9017	2954	15029	16983	0,39	0,18	1,94	7,39	7,98	10,12	0,90	0,87	17,01	18,42	
	4,80	2,90	5046	4005	9051	2954	14995	16949	0,39	0,18	1,94	7,70	8,32	10,47	0,90	0,87	17,53	18,95	
	5,05	2,90	5054	4015	9068	2946	14985	16932	0,39	0,18	1,94	8,12	8,77	10,72	0,90	0,87	18,19	19,61	
	5,30	2,90	5073	4030	9103	2927	14970	16897	0,39	0,18	1,94	8,55	9,22	10,97	0,90	0,87	18,84	20,27	
	5,60	2,85	5099	4057	9155	2901	14943	16845	0,39	0,18	1,94	9,05	9,77	11,22	0,90	0,88	19,63	21,06	
5,90	2,80	5117	4065	9182	2883	14935	16818	0,39	0,18	1,94	9,56	10,30	11,47	0,90	0,88	20,41	21,85		
SLEEPER CAB	WB	AE ⁵⁾	Front	Rear	Total	Front	Rear	Total	AC	CB ⁶⁾	CH ⁷⁾	BL ⁸⁾	BL	TL	HA ⁹⁾	HA ¹⁰⁾	TK ¹¹⁾	TW ¹²⁾	
	4,20	2,40	5210	3867	9077	2790	15133	16923	0,82	0,16	1,94	5,99	6,54	9,37	0,90	0,87	15,97	17,36	
	4,40	2,55	5222	3929	9151	2778	15071	16849	0,82	0,16	1,94	6,32	6,89	9,72	0,90	0,87	16,49	17,89	
	4,60	2,75	5218	3972	9190	2782	15028	16810	0,82	0,16	1,94	6,64	7,25	10,12	0,90	0,87	17,01	18,42	
	4,80	2,90	5218	4006	9224	2782	14994	16776	0,82	0,16	1,94	6,97	7,59	10,47	0,90	0,87	17,53	18,95	
	5,05	2,90	5226	4016	9241	2774	14984	16759	0,82	0,16	1,94	7,41	8,04	10,72	0,90	0,87	18,19	19,61	
	5,30	2,90	5245	4032	9277	2755	14968	16723	0,82	0,16	1,94	7,82	8,51	10,97	0,90	0,87	18,84	20,27	
	5,60	2,85	5271	4058	9329	2729	14942	16671	0,82	0,16	1,94	8,35	9,06	11,22	0,90	0,87	19,63	21,06	
	5,90	2,80	5289	4066	9355	2711	14934	16645	0,82	0,16	1,94	8,86	9,60	11,47	0,90	0,88	20,41	21,85	
SPACE CAB	WB	AE ⁵⁾	Front	Rear	Total	Front	Rear	Total	AC	CB ⁶⁾	CH ⁷⁾	BL ⁸⁾	BL	TL	HA ⁹⁾	HA ¹⁰⁾	TK ¹¹⁾	TW ¹²⁾	
	4,20	2,40	5321	3869	9190	2679	15131	16810	0,82	0,16	2,62	6,04	6,59	9,37	0,90	0,87	15,97	17,36	
	4,40	2,55	5334	3930	9264	2666	15070	16736	0,82	0,16	2,62	6,37	6,95	9,72	0,90	0,87	16,49	17,89	
	4,60	2,75	5330	3973	9303	2670	15027	16697	0,82	0,16	2,62	6,70	7,31	10,12	0,90	0,87	17,01	18,42	
	4,80	2,90	5330	4007	9337	2670	14993	16663	0,82	0,16	2,62	7,04	7,66	10,47	0,90	0,87	17,53	18,95	
	5,05	2,90	5338	4017	9354	2662	14983	16646	0,82	0,16	2,62	7,46	8,11	10,72	0,90	0,87	18,19	19,61	
	5,30	2,90	5357	4032	9390	2643	14968	16610	0,82	0,16	2,62	7,89	8,58	10,97	0,90	0,87	18,84	20,27	
	5,60	2,85	5383	4058	9442	2617	14942	16558	0,82	0,16	2,62	8,42	9,13	11,22	0,90	0,87	19,63	21,06	
	5,90	2,80	5402	4066	9468	2598	14934	16532	0,82	0,16	2,62	8,93	9,70	11,47	0,90	0,88	20,41	21,85	

OTHER DIMENSIONS	VA: 1,37	WN: 1,40	HV ¹³⁾ : 1,02	HV ¹⁴⁾ : 0,97	RB: 0,79	SB: 1,82	TB ¹⁵⁾ : 2,48
------------------	----------	----------	--------------------------	--------------------------	----------	----------	--------------------------

1) GVM in conformity with registration documents.

2) GCM in conformity with registration documents.

3) Axle load with standard tyre size.

4) Chassis and cab weight calculated with: Standard specification items only with 340 litres of fuel, 50 litres of AdBlue® and driver of 90 kg, tolerance ± 3%. Changing of the specification can have major impact on vehicle weight.

5) Other AE dimensions may be available for shown WB. Modify rear overhang to the calculated body length.

6) CB is based on standard air intake and/or exhaust.

7) Cab height is measured from frame member to closed cab roof hatch. With air intake on cab roof add: 0.14 m (for MX-11); add 0.21 m for MX-13.

8) Calculate customer specific body length with TOPEC. Body lengths shown based on evenly distributed load at max axle load.

9) Unladen height at centre of driven axle (trailing axle down).

10) Laden height at centre of driven axle(s).

11) TK = turning circle between kerbs.

12) TW = turning circle between walls.

13) Unladen height at centre of front axle(s).

14) Laden height at centre of front axle(s).

15) TB is overall width at rear. (At lower cab step 255).

Depending on the vehicle configuration a specific option may not be possible. The availability and specification of this vehicle may differ per country. For further information please contact the DAF organisation. Pictures and technical illustrations are not binding in detail and can differ from the standard specification. Subject to modification without prior notice.

A PACCAR COMPANY DRIVEN BY QUALITY

DAF

016F6626AAAA - 2021371 - 11-06-2021