


Specification sheet

XG⁺ 450

FA 4X2 Rigid, Low Deck



ENGINES

- XG+ NewGen 450 MX-11 (330 kW / 449 hp)
- XG+ NewGen 430 MX-13 (315 kW / 428 hp)
- XG+ NewGen 480 MX-13 (355 kW / 483 hp)
- XG+ NewGen 530 MX-13 (390 kW / 530 hp)

GVM¹⁾

- 18000 kg
-
- Max. front 7500 kg
- Max. rear 11500 kg

GCM²⁾

- 44000 kg
-
-
-

016F0309BBAA - 202545A - 15-07-2025

DAF Trucks Ltd, UK, Haddenham, HP17 8LJ, www.daf.co.uk

CAB EXTERIOR

Luxurious cab for XG+ series, with unrivalled aerodynamics for fuel efficient driving and low CO2 emissions. The huge and deep frontscreen, curved at the sides, and the large side windows offer an unsurpassed direct view for the driver, to enhance road safety. The cab interior is extremely comfortable for driving, living and sleeping with unprecedented spaciousness and practical layout. Cab length: 2690 mm; cab width: 2500 mm. Number of cab entrance steps: 3.; Cab suspension air; LED head, cornering and fog lights; Front view mirror.

Optional

02941 Chassis front execution: bottom plate	06629 Two hazard beacon lights
03358 External sun visor	03232 Front windscreen with solar control foil
01015 LED Skylights; aux. LED lights on cab rf, prepared	01550 No front view mirror
01925 Two LED work lamps for cab rear wall	01358 No DAF Digital Vision System
01891 Hazard beacons on cab front, prepared	01913 DAF Corner View

AERODYNAMICS

Optional

03846 No roof air deflector	04906 Side collars, one side hinged
01581 Adj. roof air deflector; over 4 m (!) for XG+ cab	03074 Side collars, both sides hinged

COLOURS

Cab colour E1980 Crystal White; Chassis colour grey.; Colour of bumper: Crystal White.

CAB INTERIOR

Cab interior trim colour: Exclusive; Dashboard finish: Plateau; Cab interior decoration: Argenta; Driver seat: Luxury Air; Arm rest at both sides of the driver seat; Co-driver seat: cinema + table; fabric cover; Dashboard table; Storage compartment with drawer in centre; Upper bunk; Automatic Cab Climate Control; Auxiliary cab heater (water); Roof hatch, electric control.

Optional

02043 Dashboard finish: Vision	02854 Xtra Comfort mattress for lower bunk
02350 Cab interior decoration: Natura	02858 Xtra Comfort mattress for adjustable lower bunk
07736 Driver seat: Super Air	01775 Xtra Comfort mattress with topper for lower bunk
07737 Driver seat: Xtra Leather Air	02380 Mattress for DAF Relax Bed
02241 Driver seat, swivel base	04150 Mattress with topper for DAF Relax Bed
04050 Refrigerator and drawer	01967 Park air conditioning, integrated
04069 Two refrigerators	

COMMUNICATION AND DRIVING MANAGEMENT

PACCAR Connect; Tachograph digital, Stoneridge version G2V2A; Speed limiter setting 85/90 km/h; Adaptive Cruise Control with FCW and AEBS-3; Driver Performance Assistant.

Optional

09681 Preparation for Maut	03684 Infotainment including DAF Truck Navigation
03470 Infotainment incl. DAF Truck Nav. and tablet prep.	

SAFETY AND SECURITY

DAF drowsiness detection; Lane Departure Warning System; Vehicle Stability Control (VSC); Basic engine immobiliser system.

Optional

08631 Air bag (driver) and 2 seat belt tensioners	00795 Safety regulations EC ADP
02569 No Driver State Monitoring	01952 No DAF Side/Turn Assist
03628 DAF drowsiness & distraction detection	

SUSPENSION AND AXLES

Front: 8.00 t, air suspension, 161N; Rear axle load 11.50 t; Rear: air suspension, SR1344.

Optional

04588 Rear axle SR1347	08191 Axle load monitoring
-------------------------------	-----------------------------------

WHEELS AND TYRES

Driven rear axle(s): 315/60R22.5; F1,315/60R22.5GO FMXSE 154/148 L Steering BBB 3P; R1,315/60R22.5GO GFDND 152/148 L Traction BBB 3P.

Optional

16152 Tyre makes and types

DRIVELINE

Engine MX-11, multi torque 6 cylinder diesel engine, 10.8 litres. Output 330 kW (449 hp) at 1600 rpm. Maximum torque 2350 Nm at 900-1125 rpm.; Exhaust emission Euro 6; Eco fuel; 12-speed TraXon 12TX2210 DD, 16.69-1.00; Gearbox ratio 16.69-1.00; Rear axle ratio 2.38.

Optional

07110 Eco performance	08371 Long Combination Vehicle (LCV)
07101 Standard transport, Lite version	09638 Off-road applications
09636 Heavy haulage	01498 Off-road applications with Rock-free function
09637 Liquid transport	02843 Mechanical differential lock

BRAKE SYSTEM

MX Engine Brake; Ventilated disc brakes front and rear. Dual circuit air system with electronic control (EBS). Engine driven, water cooled aire compressor with automatic air heated dryer..

Optional

02715 ZF Intarder	01497 Park brake control pneumatic with spoken warning
01572 Park brake control electro-pneumatic	

CHASSIS

Wheelbase 4.90 m / rear overhang 2.35 m; Side member height 260 mm; Standard component location; 340 l alu fuel tank LH, height 505 mm; Tank for AdBlue® 45 l, left-hand side chassis; Front underrun protection (FUP); Spray suppression.

Optional

16157 Fuel tanks, material and sizes	03322 Rear light with bulbs
07071 Spare wheel carrier right-hand side	

DRAWBAR AND TRAILER EQUIPMENT

D-value cross member D=13.7; Pneumatic trailer connection C-type;
Electric connection 24 V / 2x7 pins.

Optional

- | | |
|---|---|
| 07033 Trailer coupling Ringfeder
D=13.7 B | 08027 Trailer coupling Rockinger
D=20.0 B |
| 07034 Trailer coupling Ringfeder
D=20.0 B | 04659 Trailer cable EBS |
| 08026 Trailer coupling Rockinger
D=13.0 B | |

BODIES AND PREPARATIONS FOR BODYING

Application connector chassis.

Optional

- | | |
|--------------------------------------|------------------------------------|
| 09421 Additional spare wiring | 08121 Tail lift application |
|--------------------------------------|------------------------------------|

POWER TAKE-OFF (PTO)

Optional

- 16148** PTO types and positions

24V POWER SUPPLY

Alternator 130 A, batteries 2x 210 Ah AGM..

Optional

- | | |
|-------------------------------|--------------------------------|
| 04873 Alternator 110 A | 06440 Batteries 2x230Ah |
| 08775 Alternator 150 A | |

GVM AND GCM

Chassis weight related technical GVM max 19500 kg; Driveline
related max GCM 44000 kg class 2.

APPLICATION CONDITIONS

Air intake front.

Optional

- | | |
|---------------------------------------|--|
| 08400 Silent mode | 06620 Anti-dust blow-up shield +
bugscreen |
| 06614 Anti-dust blow-up shield | |

SERVICE AND MAINTENANCE

Standard Warranty takes care of 1 year complete vehicle as supplied
by the OEM (excl. real wear parts), 2nd year driveline and 1st year
breakdown.; ITS service.

Optional

- 08311** Service interval extended

VEHICLE DELIVERY

Minimum toolkit.

Optional

- 07569** Lifting jack

OPTION PACKAGES


Optional

- | | |
|------------------------------------|---------------------------|
| 17448 Safety pack | 17625 Climate Pack |
| 17596 Executive Pack XG/XG+ | |

Go to **DAF.com** to configure your own perfect DAF.

XG⁺ 450

FA 4X2 Rigid, Low Deck



1) GVM in conformity with registration documents.

2) GCM in conformity with registration documents.

3) Axle load with standard tyre size.

4) Chassis and cab weight calculated with: Standard specification items only with 340 litres of fuel, 45 litres of AdBlue® and driver of 90 kg, tolerance ± 3%. Changing of the specification can have major impact on vehicle weight.

5) Other AE dimensions may be available for shown WB. Modify rear overhang to the calculated body length.

6) CB is based on standard air intake and/or exhaust.

7) Cab height is measured from frame member to closed cabin roof hatch.

8) Calculate customer specific body length with TOPEC. Body lengths shown based on evenly distributed load at max axle load.

9) Unladen height at centre of driven axle(s).

10) Laden height at centre of driven axle(s).

11) TK = turning circle between kerbs.

12) TW = turning circle between walls.

13) Unladen height at centre of front axle(s).

14) Laden height at centre of front axle(s).

15) TB is overall width at rear. (At centre of front axle 255).

Depending on the vehicle configuration a specific option may not be possible. The availability and specification of this vehicle may differ per country. For further information please contact the DAF organisation. Pictures and technical illustrations are not binding in detail and can differ from the standard specification. Subject to modification without prior notice.